

Axminster 7 x 7

Belgotex®

Construction	Woven cut pile carpet
Yarn	80% Wool / 20% Nylon
Wool Content	40% Wools of New Zealand / 40% British Wool
Nylon Content	6.6 BCF Nylon
Width	Any width up to 4.0m
Yarn Weight	1131g/m ² / 34oz/yd ²
Total Weight	2200g/m ²
Pile Height	7.0mm
Total Thickness	10.0mm
Yarn Ply	3-ply
Pitch	27.6 rows per 10cm (7 rows per inch)
Beat-up	27.6 ends per 10cm (7 ends per inch)
Backing	Woven Jute / Polyester / Cotton with Latex
Electrical Properties	Antistatic
Electrical Propensity	< 3.5kV (AATCC134)
Fire Rating	7.4kW/m ² (ISO 9239-1:2002) Class 1 (ASTME648 (CRF)) Pass (BS4790 (Hot Metal Nut)) Pass (ASTME662 (Smoke Development)) 68.7 (MJ/M2 (Fire Load Density))
VOC Rating	GLP Certification
Resistance to Microorganisms	Insect Resistance Class 5 (WNZTM27)
Colour Fastness	> Class 4 (ISO 4892-2 1994)
Stain Resistance	3M Scotchgard
Rating	Extra Heavy Duty Residential / Heavy Duty Commercial
Stair Rating	Suitable
Custom Design / Colour	Any colour, any design
ESD Certification	ISO 14001:2004
Manufacturers Certification	Authorised Wools of New Zealand Brand Partner (ISO 9001:2000)
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

B.

0800 377 753 | belgotex.co.nz

info@belgotex.co.nz

12/09/18

Axminster 7 x 8

Belgotex®

Construction	Woven cut pile carpet
Yarn	80% Wool / 20% Nylon
Wool Content	40% Wools of New Zealand / 40% British Wool
Nylon Content	6.6 BCF Nylon
Width	Any width up to 4.0m
Yarn Weight	1267g/m ² / 38oz/yd ²
Total Weight	2300g/m ²
Pile Height	7.0mm
Total Thickness	11.0mm
Yarn Ply	3-ply
Pitch	27.6 rows per 10cm (7 rows per inch)
Beat-up	31.5 ends per 10cm (8 ends per inch)
Backing	Woven Jute / Polyester / Cotton with Latex
Electrical Properties	Antistatic
Electrical Propensity	< 3.5kV (AATCC134)
Fire Rating	7.4kW/m ² (ISO 9239-1:2002) Class 1 (ASTME648 (CRF)) Pass (BS4790 (Hot Metal Nut)) Pass (ASTME662 (Smoke Development)) 68.7 (MJ/M2 (Fire Load Density))
VOC Rating	GLP Certification
Resistance to Microorganisms	Insect Resistance Class 5 (WNZTM27)
Colour Fastness	> Class 4 (ISO 4892-2 1994)
Stain Resistance	3M Scotchgard
Rating	Extra Heavy Duty Residential / Extra Heavy Duty Commercial
Stair Rating	Suitable
Custom Design / Colour	Any colour, any design
ESD Certification	ISO 14001:2004
Manufacturers Certification	Authorised Wools of New Zealand Brand Partner (ISO 9001:2000)
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

B.

0800 377 753 | belgotex.co.nz

info@belgotex.co.nz

12/09/18

Construction	Woven cut pile carpet
Yarn	80% Wool / 20% Nylon
Wool Content	40% Wools of New Zealand / 40% British Wool
Nylon Content	6.6 BCF Nylon
Width	Any width up to 4.0m
Yarn Weight	1403g/m ² / 42oz/yd ²
Total Weight	2350g/m ²
Pile Height	7.0mm
Total Thickness	11.0mm
Yarn Ply	3-ply
Pitch	27.6 rows per 10cm (7 rows per inch)
Beat-up	35.43 ends per 10cm (9 ends per inch)
Backing	Woven Jute / Polyester / Cotton with Latex
Electrical Properties	Antistatic
Electrical Propensity	< 3.5kV (AATCC134)
Fire Rating	7.4kW/m ² (ISO 9239-1:2002) Class 1 (ASTME648 (CRF)) Pass (BS4790 (Hot Metal Nut)) Pass (ASTME662 (Smoke Development)) 68.7 (MJ/M2 (Fire Load Density))
VOC Rating	GLP Certification
Resistance to Microorganisms	Insect Resistance Class 5 (WNZTM27)
Colour Fastness	> Class 4 (ISO 4892-2 1994)
Stain Resistance	3M Scotchgard
Rating	Extra Heavy Duty Residential / Extra Heavy Duty Commercial
Stair Rating	Suitable
Custom Design / Colour	Any colour, any design
ESD Certification	ISO 14001:2004
Manufacturers Certification	Authorised Wools of New Zealand Brand Partner (ISO 9001:2000)
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Axminster 7 x 10

Belgotex®

Construction	Woven cut pile carpet
Yarn	80% Wool / 20% Nylon
Wool Content	40% Wools of New Zealand / 40% British Wool
Nylon Content	6.6 BCF Nylon
Width	Any width up to 4.0m
Yarn Weight	1560g/m ² / 46oz/yd ²
Total Weight	2350g/m ²
Pile Height	7.0mm
Total Thickness	11.0mm
Yarn Ply	3-ply
Pitch	27.6 rows per 10cm (7 rows per inch)
Beat-up	35.43 ends per 10cm (9 ends per inch)
Backing	Woven Jute / Polyester / Cotton with Latex
Electrical Properties	Antistatic
Electrical Propensity	< 3.5kV (AATCC134)
Fire Rating	7.4kW/m ² (ISO 9239-1:2002) Class 1 (ASTME648 (CRF)) Pass (BS4790 (Hot Metal Nut)) Pass (ASTME662 (Smoke Development)) 68.7 (MJ/M2 (Fire Load Density))
VOC Rating	GLP Certification
Resistance to Microorganisms	Insect Resistance Class 5 (WNZTM27)
Colour Fastness	> Class 4 (ISO 4892-2 1994)
Stain Resistance	3M Scotchgard
Rating	Extra Heavy Duty Residential / Extra Heavy Duty Commercial
Stair Rating	Suitable
Custom Design / Colour	Any colour, any design
ESD Certification	ISO 14001:2004
Manufacturers Certification	Authorised Wools of New Zealand Brand Partner (ISO 9001:2000)
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

B.

0800 377 753 | belgotex.co.nz

info@belgotex.co.nz

12/09/18

Axminster 7 x 11

Belgotex®

Construction	Woven cut pile carpet
Yarn	80% Wool / 20% Nylon
Wool Content	40% Wools of New Zealand / 40% British Wool
Nylon Content	6.6 BCF Nylon
Width	Any width up to 4.0m
Yarn Weight	1675g/m ² / 50oz/yd ²
Total Weight	2700g/m ²
Pile Height	7.0mm
Total Thickness	11.0mm
Yarn Ply	3-ply
Pitch	27.6 rows per 10cm (7 rows per inch)
Beat-up	43.3 ends per 10cm (11 ends per inch)
Backing	Woven Jute / Polyester / Cotton with Latex
Electrical Properties	Antistatic
Electrical Propensity	< 3.5kV - AATCC134
Fire Rating	7.4kW/m ² (ISO 9239-1:2002) Class 1 (ASTME648 (CRF)) Pass (BS4790 (Hot Metal Nut)) Pass (ASTME662 (Smoke Development)) 68.7 (MJ/M2 (Fire Load Density))
VOC Rating	GLP Certification
Resistance to Microorganisms	Insect Resistance Class 5 (WNZTM27)
Colour Fastness	> Class 4 (ISO 4892-2 1994)
Stain Resistance	3M Scotchgard
Rating	Extra Heavy Duty Residential / Extra Heavy Duty Commercial
Stair Rating	Suitable
Custom Design / Colour	Any colour, any design
ESD Certification	ISO 14001:2004
Manufacturers Certification	Authorised Wools of New Zealand Brand Partner (ISO 9001:2000)
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

B.

0800 377 753 | belgotex.co.nz

info@belgotex.co.nz

12/09/18