

# Armstrong RH99 Fine Fissured ceiling tiles

## - Green Building Summary Sheet -

### Author

EnviroSpec Verification Services





### Document Type

Green Building Rating Compatibility Analysis

### Document Code

ES-GSNZ-09-11i

### Validity

			
Office 2009 + V3 ✓ Interiors 2009 + V3 ✓ Education 2009 + V3 + V3.1 ✓ Industrial 2009 + V3 ✓	Homestar V2 + V3 ✓	N/A -	N/A -

### Client


Forman Building Systems

### Product Name

Armstrong Fine Fissured (inc. High NRC) Ceiling Tiles

### Product Description

Armstrong RH99 Fine Fissured is a medium absorption acoustic ceiling panel for suspended ceiling grid which combines a high level of acoustic absorption with exceptional impact and scratch resistant because of the factory applied paint finish over an acoustically transparent Durabrite tissue. This product is GreenTag Green Rate Level A certified as well as low VOC and low Formaldehyde as tested by CETEC based on Greenguard requirements and combines HumiGuard HumiGuard Plus no sag performance with BioBlock paint to inhibit surface growth of mold and mildew. Fine fissured has a NRC of 0.55 and a CAC of 30. Forman also offers Armstrong Fine fissured with High acoustic ratings with a NRC of 0.70 and CAC of 40 for superior performance.



### Manner in which the product may contribute towards points

### Legend of Symbols in EnviroSpec

Products must meet specific criteria (e.g. Paint VOC emissions, carpets, etc)



Products may help achieve points by their very nature, if they are specified and installed (e.g. bicycle racks)



Products may help achieve an outcome but they must be used in a specific manner (e.g. lighting control and zoning systems) OR This product can contribute towards the outcome but many other products or factor influence that same outcome (E.g. Potable Water Calculator)



### Disclaimer - Please read this carefully

Each Building Environmental Rating Tool and Scheme nominated herein is owned and operated by its respective operative organisation, independently of EnviroSpec Ltd., and EnviroSpec Ltd. equally operates independently of any nominated rating scheme. The information represented on EnviroSpec is not endorsed by any of these organisations in a direct manner and any decision regarding final approval or refusal of points and certifications where the nominated product is used is at the final discretion of the respective owners and operators of the nominated Building Environmental Rating Schemes, and any network of assessors or auditors that are accredited to operate under their assessment structure, in accordance with all associated technical manuals, rules and guidelines. For detailed technical information about each Building Environmental Rating Schemes and product related criteria please refer to the appropriate technical manuals. EnviroSpec does not accept liability for any loss or damages resulting from the use of this document and emphasizes that this document is provided as guidance only. Use of, or reliance upon, any information contained in this report is at the user's own risk. The information presented in this report is valid for the Building Environmental Rating Schemes and Tools nominated herein only. As and when the respective owners and operators publish updates or new tools, the information may require updating. EnviroSpec Ltd. will only update information in this report upon receiving written consent from the Manufacturer, Supplier or upon request from an operative organisation of one of the Building Environmental Rating Tools nominated herein. **It is the responsibility of the reader to check for regular updates.**

## Armstrong RH99 Fine Fissured ceiling tiles

### - Green Building Summary Sheet -

Tool	Credit category	Points available	Requirements	Contribution symbol	Contribution Potential	Details of compliance
Green Star NZ Office 2009	IEQ - 8	3	This credit rewards buildings that maximize daylight.	○	Contributing factor	Armstrong Fine Fissured Ceiling tiles have a Light Reflectance Value of 85% (average) which may help improve the floor area with a daylight factor above 2.5%.
	IEQ - 11	3	This credits rewards for good visual comfort and lighting design.	✓ ○	2 (Contributing factor)	Armstrong Fine Fissured Ceiling tiles have a Light Reflectance Value of 85% (average), thus satisfying this requirement. The remaining items in this credit are based on lighting design and are not product dependent.
	IEQ - 13	2	This credit rewards buildings that maintain adequate noise levels.	○	Contributing factor	Armstrong Fine Fissured Ceiling tiles have a CAC of 30 and NRC of 0.55 (40 and 0.70 respectively for the high NRC version) which may assist in maintaining suitable noise levels
	ENE - 4	3	This credit rewards design options that lessen lighting energy consumption while maintaining adequate lighting levels	○	Contributing factor	Armstrong Fine Fissured Ceiling tiles have a Light Reflectance Value of 85% (average) which may assist in reducing the lighting output required to obtain a given lighting level in a space.
	MAT - K	2	This credit rewards the use of eco-preferred and/or low VOC/formaldehyde emitting products for ceilings engineered wood products and gypsum plasterboard.	✓	2 Points	The nominated product is GreenTag Green Rate Level A certified, thus satisfying the full point requirements for ceiling tiles.
Education 2009 + V3	IEQ - 8	3	This credit rewards buildings that maximize daylight.	○	Contributing factor	Armstrong Fine Fissured Ceiling tiles have a Light Reflectance Value of 85% (average) which may help improve the floor area with a daylight factor above 2.5%.
	IEQ - 11	3	This credits rewards for good visual comfort and lighting design.	✓ ○	2 points (Contributing factor)	Armstrong Fine Fissured Ceiling tiles have a Light Reflectance Value of 85% (average), thus satisfying this requirement. The remaining items in this credit are based on lighting design and are not product dependent.
	IEQ - 13	2	This credit rewards buildings that maintain adequate noise levels.	○	Contributing factor	Armstrong Fine Fissured Ceiling tiles have a CAC of 30 and NRC of 0.55 (40 and 0.70 respectively for the high NRC version) which may assist in maintaining suitable noise levels.
	MAT - B	3	<b><u>When used for Ceiling tiles:</u></b> * Ceiling tiles without finish required (i.e. Prefinished approved eco-label certified ceiling tiles) = 3 points. ** Ceiling tiles requiring additional paint or finish = 1.5 points (with the additional 1.5 points achievable if the paint/finish also has an approved eco label.)	✓	Up to 3 points (unweighted product calculator score)	The nominated product is GreenTag Green Rate Level A certified, thus satisfying the full point requirements for ceiling tiles.

## Armstrong RH99 Fine Fissured ceiling tiles

### - Green Building Summary Sheet -

Industrial 2009	IEQ - 8	3	This credit rewards buildings that maximize daylight.	○	Contributing factor	Armstrong Fine Fissured Ceiling tiles have a Light Reflectance Value of 85% (average) which may help improve the floor area with a daylight factor above 2.5%.
	IEQ - 11	3	This credits rewards for good visual comfort and lighting design.	✓ ○	2 (Contributing factor)	Armstrong Fine Fissured Ceiling tiles have a Light Reflectance Value of 85% (average), thus satisfying this requirement. The remaining items in this credit are based on lighting design and are not product dependent.
	IEQ - 13	2	This credit rewards buildings that maintain adequate noise levels.	○	Contributing factor	Armstrong Fine Fissured Ceiling tiles have a CAC of 30 and NRC of 0.55 (40 and 0.70 respectively for the high NRC version) which may assist in maintaining suitable noise levels
	MAT - K	2	This credit rewards the use of eco-preferred and/or low VOC/formaldehyde emitting products for ceiling tiles, engineered wood products and gypsum plasterboard	✓	2 Points	The nominated product is GreenTag Green Rate Level A certified, thus satisfying the full point requirements for ceiling tiles.
Interiors 2009	IEQ - 8	3	This credit rewards buildings that maximize daylight.	○	Contributing factor	Armstrong Fine Fissured Ceiling tiles have a Light Reflectance Value of 85% (average) which may help improve the floor area with a daylight factor above 2.5%.
	IEQ - 11	3	This credits rewards for good visual comfort and lighting design. To achieve 2 point or more, the light reflectance of Ceilings must be minimum 75%.	✓ ○	2 (Contributing factor)	Armstrong Fine Fissured Ceiling tiles have a Light Reflectance Value of 85% (average), thus satisfying this requirement. The remaining items in this credit are based on lighting design and are not product dependent.
	IEQ - 13	2	This credit rewards buildings that maintain adequate noise levels.	○	Contributing factor	Armstrong Fine Fissured Ceiling tiles have a CAC of 30 and NRC of 0.55 (40 and 0.70 respectively for the high NRC version) which may assist in maintaining suitable noise levels.
	ENE- 4	3	This credit rewards design options that lessen lighting energy consumption while maintaining adequate lighting levels.	○	Contributing factor	Armstrong Fine Fissured Ceiling tiles have a Light Reflectance Value of 85% (average) which may assist in reducing the lighting output required to obtain a given lighting level in a space.
	MAT - B	7	<u>When used for Ceiling tiles:</u> "Ceiling tiles without finish required (i.e. Prefinished approved eco-label certified ceiling tiles) = 7 points." "Ceiling tiles requiring additional paint or finish = 3.5 points (with the additional 3.5 points achievable if the paint/finish also has an approved eco label.)"	✓	Up to 7 points (unweighted product calculator score)	The nominated product is GreenTag Green Rate Level A certified, thus satisfying the full point requirements for ceiling tiles

## Armstrong RH99 Fine Fissured ceiling tiles

### - Green Building Summary Sheet -

<b>Green Star NZ</b>  <b>Office V3.0</b> + <b>Education V3.1</b> + <b>Industrial V3</b> + <b>Interiors V3</b>	IEQ - 8	3	This credit rewards buildings that maximize daylight.	○	Contributing factor	Armstrong Fine Fissured Ceiling tiles have a Light Reflectance Value of 85% (average) which may help improve the floor area with a daylight factor above 2.5%
	IEQ - 11	3	This credits rewards for good visual comfort and lighting design.	✔ ○	2 (Contributing factor)	Armstrong Fine Fissured Ceiling tiles have a Light Reflectance Value of 85% (average), thus satisfying this requirement. The remaining items in this credit are based on lighting design and are not product dependent.
	IEQ - 13	2	This credit rewards buildings that maintain adequate noise levels.	○	Contributing factor	Armstrong Fine Fissured Ceiling tiles have a CAC of 30 and NRC of 0.55 (40 and 0.70 respectively for the high NRC version) which may assist in maintaining suitable noise levels.
	ENE - 4	3	This credit rewards design options that lessen lighting energy consumption while maintaining adequate lighting levels	○	Contributing factor	Armstrong Dune and Dune Max Ceiling tiles have a Light Reflectance Value of 85% (average) which may assist in reducing the lighting output required to obtain a given lighting level in a space
	MAT - 4	2	This credit rewards the use of eco-preferred and/or low VOC/formaldehyde emitting products for ceilings engineered wood products and gypsum plasterboard.	✔	2 Points	The nominated product is GreenTag Green Rate Level A certified, thus satisfying the full point requirements for ceilings.
<b>Homestar V2+V3</b>	MAT -1	9	This credit rewards the use selection of eco-preferred and responsibly sourced materials. Ceilings are amongst thirteen possible construction types eligible for 1 merit each	✔	1 Merit	The nominated products are GreenTag GreenRate Level A certified and satisfy the requirements for this credit.
	EHC-9	2	This credit rewards the provision of an improved sound environment in accordance with items listed in the sound insulation checklist.	✔	0.29/0.33	Acoustic ceiling tiles are referred to in the sound insulation checklist. If the nominated ceiling tiles are used in > 80% of a dwelling's livable rooms then 0.29 points can be claimed in Homestar V2 and 0.33 points can be claimed in Homestar V3.
<b>Living Building Challenge</b>		Pass/Fail	This product has not been assessed against this criteria.	-	-	N/A
<b>SBN Circular Economy Office Model V1.1</b>		Pass/Fail	This product has not been assessed against this criteria.	-	-	N/A