

Declare.

DURASEIN® SOLID SURFACE DURASEIN®

Final Assembly: Zhuhai City, Jinwan District, China

Life Expectancy: 50+ (Warranty life of 10 years) Year(s)

Embodied Carbon: 5.54 E+03 kg CO₂eq

Declared Unit: 1m³

End of Life Options: Salvageable/Reusable in its Entirety,
Recyclable (100%), Landfill (100%)

EU CoC Screened: Does Not Contain

Ingredients:

ALUMINA TRIHYDRATE: Aluminum hydroxide; **POLYMETHYL METHACRYLATE (PMMA):** Polymethyl methacrylate; **TITANIUM DIOXIDE:** Titanium dioxide; **ULTRAMARINE BLUE:** C.I. Pigment Blue 29; **IRON(III) OXIDE:** Iron oxide; **PIGMENT YELLOW 151:** Benzoic acid, 2-[[1-[[[(2,3-dihydro-2-oxo-1H-benzimidazol-5-yl)amino]carbonyl]-2-oxopropyl]azo]-]; **BAYFERROX 4905:** C.I. Pigment Yellow 42

Living Building Challenge Criteria: Compliant

I-13 Red List:

- LBC Red List Free % Disclosed: 100% at 100ppm
 LBC Red List Approved VOC Content: Not Applicable
 Declared

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

DRS-0001

EXP. 01 DEC 2025

SCREENED: 22 NOV 2024

Original Issue Date: 2023